Product	GD800 Comparable Coin Validator(Top Entry)
Specification	Input Voltage: DC+12V±20% Work Temperature: -10°C~+75°C Output: Pulse
Coin acceptance	1 coin acceptance Coin diameter: φ18mm~27mm Coin thickness: 1.5mm~2.6mm
Box Package	Packed:50 pcs/box Size:58*33*28CM/box Measurement: 0.072116m³/box
Single Package	Weight:0.36kg/pc Size:11*12.5*6cm/pc

Product View





Operation


Cable Interface

1. Yellow parts → Remove the Backward and Replace Coin as Sample Coin. Same accept . Different, reject.

- 2. N.C. \rightarrow white line \rightarrow Normal Close
- N.O. → gree line →Normal Open→ Select N.O. or N.C. to fit different machine 3. VR TURN. Adjust Coin Recognition Accuracy at SW2
- 4. brown line.+ yellow line → Counter
- 5. red line \rightarrow DC +12V.
- 6. black line—GND
- 7. Switch to "SW1":

Fast: 20ms/short pulse signal (Apply to Mario Machine) Medium: 40ms/medium pulse signal (Apply to different machine) Slow: 60ms/long pulse signal (Apply to entertainment machine)





History	the model 2006 into market,7 years,Elite model
Application	Vending machine,gaming machine,jukebox,coinbox,cyber café,arcade crane,etc.
Standard	European standard
Brand	Gondu